

Tiablo A1 LED Flashlight instructions

Profile

- I.....specifications
- II..... How to install the flashlight with illustration
- III..... Accessories, after sale service and warranty
- IV..... Remarks, common problems and solutions



I. Specifications

1. New LUXEON Rebel 0100 LED 350mA at 100 Lumens.
2. Step up and down constant current driver. High efficiency with dual mode DC-DC regulator (PWM / PFM), working voltage is 0.7V to 2.4V.
3. Output: 350mA at 100 Lumens for 3.5 hours
4. Supports one AAA battery
5. Length 7.7cm x Diameter 1.6cm
6. Type-III hard anodize. Aircraft grade aluminum T7075. Gun Metal Grey
7. Water proof to 5m, approximately 15 Feet.
8. Toughened ultra clear glass lens with AR coating.
9. Twist switch
10. 18.5-gram weight, less than ½ oz, excluding battery

II. How to install the flashlight with illustration



Tiablo flashlights are designed and manufactured by Tiablo with strict quality control. Easy to use:
Screw off the tailcap, insert the battery in the housing, anode towards head, screw on the tailcap, and then twist the head to light up.

III Accessories, after sale service and warranty

1. Accessories: Instructions, three O-rings
2. After sale service and warranty:

Tiablo will replace any flashlight with a manufacture's defect, during a period of three years. Improper use, misuse, or abuse, will void the warranty and Tiablo's liability will remain limited to the cost of the product.

IV Remarks, common problems and solutions

Remarks:

1. Install AAA battery anode towards LED
2. Avoid direct contact with the reflector
3. Long term storage of the flashlight, remove the battery and keep the housing dry.
4. Disassembly of the circuit will void the warranty.

Common problems and solutions:

1. Installed the battery and fails to light:
 - i. Verify if the battery is in the correct direction.
 - ii. Check if battery is charged.
2. If additional support is needed, kindly contact us or your local distributor.

Your satisfaction is Tiablo's pride.

www.tiablolight.com